

**L-Band Radar Transistor - GaN**

- GaN on SiC HEMT Technology
- $P_{OUT-PK} \geq 250W @ 300us/10\%/50V$
- 1.2-1.4GHz Instantaneous Operating Frequency Range
- Internal Impedance Pre-matched Device
- Depletion Mode Device
- Negative Gate Voltage and Bias Sequencing Required
- Specified For Use Under Class AB Operation
- Metal Based Package Sealed With Ceramic-Epoxy Lid
- Gold Metallization System: Chip - Wire Bond - Package
- Package Size: W=0.800" (20.32mm), L=0.400" (10.16mm)
- 100% High Power RF Tested in Broadband RF Test Fixture




PARAMETER	SYM	MIN	TYP	MAX	UNITS	TEST CONDITIONS
<b>DC ELECTRICAL SPECIFICATIONS</b>						
Drain Leakage Current	$I_{D-OFF}$	--	--	2.0	mA	$V_{DS}=50V, V_{GS}=-6V, T_{F1}, S1$
Gate Threshold Voltage	$V_{GS-TH}$	--	-2.8	--	V	$V_{DS}=50V, I_D=100mA, T_{F1}, BD$
<b>RF ELECTRICAL SPECIFICATIONS</b>						
Input Return Loss	IRL	-18	-12	-7	dB	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
Power Output	POUT	250	320	451	W	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
Power Gain	Gp	14.4	15.5	17.0	dB	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
Drain Efficiency	$N_D$	50	60	75	%	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
Pulse Amplitude Droop	D	-0.50	-0.25	+0.20	dB	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
Load Mismatch Stability	VSWR-S	2:1	--	--	--	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
Load Mismatch Tolerance	LMT	3:1	--	--	--	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, F2, F3, $T_{F1}, S1$
<b>DC &amp; RF TEST CONDITIONS</b>						
Input Power 1	PIN1	--	9	--	W	--
Drain Supply Voltage 1	V1	--	--	50.0	V	--
Quiescent Drain Current 1	$I_{DQ1}$	--	--	100	mA	--
Pulse Width 1	PW1	--	--	300	us	--
Duty Factor 1	DF1	--	--	10	%	--
Frequency 1	F1	--	1.20	--	GHz	--
Frequency 2	F2	--	1.30	--	GHz	--
Frequency 3	F3	--	1.40	--	GHz	--
Flange Temperature 1	$T_{F1}$	25	30	35	°C	--
Screening Level 1	S1	100	--	--	%	--

PARAMETER	SYM	MIN	MAX	UNITS	SCREEN	CONDITIONS
<b>MAXIMUM RATINGS</b>						
Drain-Source Voltage	$V_{DS}$	--	60	V	BD	$T_F = 25^\circ\text{C}$
Gate-Source Voltage	$V_{GS}$	-10	0	V	BD	$T_F = 25^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55	+150	$^\circ\text{C}$	BD	--
Operating Junction Temperature	$T_J$	-55	+200	$^\circ\text{C}$	BD	--
<b>PROCESS SPECIFICATIONS</b>						
DC Wafer Probe	--	--	--	--	100%	Per Integra Spec
Wafer DC, RF Qualification	--	--	--	--	Q1	Per Integra Spec
Wire Bond Strength	--	--	--	--	LM	Per Integra Spec
Pre-cap Visual Inspection	--	--	--	--	100%	Per Integra Spec
Gross Leak Test – MIL-STD-750D	--	--	--	--	100%	Method 1071.6 C
<b>THERMAL RESISTANCE</b>						
Peak Thermal Resistance Per Rated RF Specification	$R_{TH(JC)}$	--	0.21	$^\circ\text{C/W}$	BD	$T_F = 25^\circ\text{C}$
<b>SCREENING LEVELS</b>						
Parameter Qualified By Design	BD	--	--	--	--	--
Parameter Qualified By 3 Pieces (min) Per Wafer	Q1	--	--	--	--	--
Parameter Qualified By Assembly Line Monitor	LM	--	--	--	--	--

RF TEST FIXTURE – BROADBAND		
▶ Broadband RF Test Fixture. Provides Device Impedance Matching to 50Ω Across the Rated Operating Frequency Range.		
▶ Electronic CAD Drawing File Available Upon Request. Includes Circuit Dimensions and Parts List.		
▶ Reference Design PCB: Rogers RT6010.2-025-1/1, 25mil, 1/1oz. copper, DK=10.2.		
FREQUENCY (GHz)	$Z_{IF}(\Omega)$	$Z_{OF}(\Omega)$
1.20	3.00 – j 1.00	4.15 – j 2.90
1.30	3.15 + j 0.25	4.40 – j 2.90
1.40	3.35 + j 1.60	4.05 – j 2.80
Impedance Definition		

PACKAGE OUTLINE DRAWING



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.395	0.405	10.03	10.29
B	0.380	0.390	9.65	9.91
C	0.795	0.805	20.19	20.45
D	0.143	0.177	3.63	4.49
E	0.115	0.125	2.92	3.17
F	0.595	0.605	15.11	15.37
G	0.053	0.065	1.35	1.65
H	0.110	0.140	0.28	0.36
I	0.110	0.140	0.28	0.36
J	0.018	0.022	0.046	0.056
K	0.295	0.305	7.49	7.74
L	0.425	0.435	10.80	11.05
M	0.035	0.045	0.89	1.14
N	0.004	0.007	0.10	0.17

PIN SCHEDULE	
D	DRAIN
S	SOURCE
G	GATE

**DEFINITIONS**

**DATA SHEET STATUS**

Proposed Specification	This data sheet contains proposed specifications.
Preliminary Specification	This data sheet contains specifications based on preliminary measurements and data.
Product Specification	This data sheet contains final product specifications.

**MAXIMUM RATINGS**

Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.

**DISCLAIMER**

Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.